



Description	Symbol	Pitch: 5	Pitch: 7.5	Pitch: 10	Pitch: 15	Pitch: 22.5	Pitch: 27.5
Carrier tape width	W	18±0.5	18±0.5	18±0.5	18±0.5	18±0.5	18±0.5
Hold down tape width	W <sub>0</sub>	9.5min	9.5min	9.5min	9.5min	9.5min	9.5min
Hole position	W <sub>1</sub>	9.0±0.5	9.0±0.5	9.0±0.5	9.0±0.5	9.0±0.5	9.0±0.5
Hold down tape position	W <sub>2</sub>	0~3.0	0~3.0	0~3.0	0~3.0	0~3.0	0~3.0
Feed hole diameter	D <sub>0</sub>	4.0±0.2	4.0±0.2	4.0±0.2	4.0±0.2	4.0±0.2	4.0±0.2
Taping pitch	P	12.7±1.0	12.7±1.0	25.4±1.0	25.4±1.0	38.1±1.0	38.1±1.0
Feed hole pitch	P <sub>0</sub>	12.7±0.2	12.7±0.2	12.7±0.2	12.7±0.2	12.7±0.2	12.7±0.2
Centering of the lead wire	P <sub>1</sub>	3.85±0.7	2.6±0.7	7.7±0.7	5.2±0.7	7.8±0.7	5.3±0.7
Centering of the body	P <sub>2</sub>	6.35±1.3	6.35±1.3	12.7±1.3	12.7±1.3	19.05±1.3	19.05±1.3
Height of component from tape center	H $\Delta$	16.5±0.3	16.5±0.5	16.5±0.5	16.5±0.5	16.5±0.5	16.5±0.5
Top edge of component	H <sub>1</sub>	32.2 max	32.2 max	39.0 max	39.0 max	44.0 max	44.0 max
Lead spacing (pitch)	F	5.0+0.8-0.2	7.5+0.8-0.2	10.0+0.8-0.2	15.0+0.8-0.2	22.5+0.8-0.2	27.5+0.8-0.2
Lead wire diameter	d	0.6±0.05	0.6±0.05	0.6±0.05	0.8±0.05	0.8±0.05	0.8±0.05
Component alignment	$\Delta$ h	0±2.0	0±2.0	0±2.0	0±2.0	0±3.0	0±3.0
Tape thickness	t	0.7±0.2	0.7±0.2	0.7±0.2	0.7±0.2	0.7±0.2	0.7±0.2